

Super Cellulosic Thinner

FOR PROFESSIONAL USE ONLY**Description**

Designed to be used with cellulosic primers and topcoats. It can also be used as a cleaning solvent.

Products and additives

Akripol 1K Priming Filler (see TDS 20.2.4)
Akripol Priming Filler AX (see TDS 20.2.2)
Senteflex Topcoat (see TDS 50.4.3)

Health and Safety

Akzo Nobel Car Refinishes recommends to provide adequate ventilation during cleaning and degreasing. In addition, wear suitable respiratory protection and suitable gloves.

Raw materials

Various solvents

Product storage and shelf life

Product shelf-life is determined by storing products in unopened packages at 20°C. As shelf life decreases with elevated storage temperature, temperatures during storage must be kept at 20-25°C range and temporary increases must not exceed 35°C, and not dip below 5°C. Prevent excessive temperature variations.



AkzoNobel Kemipol
KemaIpaşa OSB Mahallesi İzmir - Ankara Yolu
Ansızca Kúme Evleri No:287
35730, KemaIpaşa - İzmir / Türkiye
Tel: +90 232 877 00 30

Health and Safety Data (Akripol Super Cellulosic Thinner)

For professional use only. See material safety data sheet and text on the label of this product. The user of this product is required to comply with the national statutory regulations for health and safety at work and waste disposal.

The effectiveness of our systems is based on laboratory research and many years' practical experience. We guarantee that the quality of the work performed with our system meets the AKZONOBEL KEMİPOL A.Ş. standards, provided that our instructions are carefully followed and the work is performed in accordance with the requirements as to good craftsmanship. We decline any responsibility if the final result is affected by factors beyond our control. The customer has to determine the suitability of the delivered products for the intended application by using the means which normally are at his disposal.

www.akripol.com.tr

AKZONOBEL KEMİPOL A.Ş. İzmir, TURKEY