


Retarder

FOR PROFESSIONAL USE ONLY**Description**

Retarder is a special additive designed to be used with 2K Topcoat, Clearcoat and Primer applications in high temperature weather conditions. It supports flow and increases flash-off times.



Akripol Retarder can be added as 9 – 10 g to 1 L ready to spray paint mixture.

Note: In case of higher temperatures and longer flash-off times needed additional Retarder can be used in the paint mixture



Use suitable respiratory protection

Akzo Nobel Car Refinishes recommends the use of a fresh air supply respirator.

Read complete TDS for detailed product information

Retarder

FOR PROFESSIONAL USE ONLY**Description**

Retarder is a special additive designed to be used with 2K Topcoat, Clearcoat and Primer applications in high temperature weather conditions. It supports flow and increases flash-off times.

Products and additives

Akripol Retarder

Topcoats Akripol 2K Topcoats

Clearcoats Akripol Clearcoats


Primers/Fillers Akripol 2K Fillers

Basic raw materials

Special solvents

Product storage

Product shelf-life is determined when products are stored unopened at 20°C.
Avoid extreme temperature fluctuation.



AkzoNobel Kemipol
Kemalpaşa OSB Mahallesi İzmir - Ankara Yolu
Ansızca Küme Evleri No:287
35730, Kemalpaşa - İzmir / Türkiye
T: +90 232 877 00 30

HEALTH & SAFETY DATA concerning Akripol Retarder and additives:

For professional use only.(See Material Safety Data Sheet). See text on the label of this product. The user of this product is required to comply with the national statutory regulations for health and safety at work and waste disposal.

The effectiveness of our systems is based on laboratory research and many years' practical experience. We guarantee that the quality of the work performed according to our system meets the AKZONOBEL KEMİPOL A.Ş standards, provided that our instructions are carefully followed and the work is performed in accordance with the requirements as to good craftsmanship. We decline any responsibility if the final result is affected by factors beyond our control. The customer has to determine the suitability of the delivered products for the intended application by using the means which normally are at his disposal.

www.akripol.com.tr

AKZONOBEL KEMİPOL A.Ş. İzmir, TÜRKİYE