

# Antisilicone

## FOR PROFESSIONAL USE ONLY

### Description

Antisilicone is a special additive to be used in vehicle refinishes in the case of silicone contamination.

### Products and additives

Antisilicone

### Additive

Antisilicone can be added in all Akripol 2K topcoats and clearcoats.  
*Do not add Antisilicone to primers, fillers or basecoats.*

### Basic Raw Materials:

Special solvents and anti-silicone agent.

### Mixing ratio by volume:

Depending on the degree of contamination, add 1 to 3 caps (child resistant closure) or 5 to 15 grams of the Antisilicone to 1 liter of paint at spraying viscosity.

### Product storage



Product shelf-life is determined when products are stored unopened at 20°C.  
Avoid extreme temperature fluctuation.



AkzoNobel Kemipol  
Kemalpaşa OSB Mahallesi İzmir - Ankara Yolu  
Ansızca Küme Evleri No:287  
35730, Kemalpaşa - İzmir / Türkiye  
T: +90 232 877 00 30

### HEALTH & SAFETY DATA concerning Akripol Antisilicone:

For professional use only.(See Material Safety Data Sheet). See text on the label of this product. The user of this product is required to comply with the national statutory regulations for health and safety at work and waste disposal.

The effectiveness of our systems is based on laboratory research and many years' practical experience. We guarantee that the quality of the work performed according to our system meets the AKZONOBEL KEMİPOL A.Ş standards, provided that our instructions are carefully followed and the work is performed in accordance with the requirements as to good craftsmanship. We decline any responsibility if the final result is affected by factors beyond our control. The customer has to determine the suitability of the delivered products for the intended application by using the means which normally are at his disposal.

[www.akripol.com.tr](http://www.akripol.com.tr)

**AKZONOBEL KEMİPOL A.Ş. İzmir, TÜRKİYE**