

# AKRİPOL 2K Acrylic Topcoat

Akripol 2K acrylic topcoat is designed for refinishes of passenger cars and commercial vehicles.

It is a 2 component acrylic topcoat that has high physical and chemical durability with high gloss levels.

It has strong hiding power that contributes to lower paint consumption and it is also easy to apply topcoat.

Akripol 2K Acrylic Topcoats do not contain Lead (Pb) containing pigments.




Features	Benefits
<ul style="list-style-type: none"> <li>No Lead containing</li> </ul>	<ul style="list-style-type: none"> <li>People and Environmental Health and Safety</li> </ul>
<ul style="list-style-type: none"> <li>Perfect flow and high gloss levels</li> </ul>	<ul style="list-style-type: none"> <li>Excellent appearance after drying</li> <li>Customer satisfaction</li> </ul>
<ul style="list-style-type: none"> <li>Easy to apply</li> </ul>	<ul style="list-style-type: none"> <li>No need for training</li> <li>Saving in process times</li> </ul>
<ul style="list-style-type: none"> <li>Wide application window</li> </ul>	<ul style="list-style-type: none"> <li>With selection of different hardeners and accelerator suitable for different type of repairs in various conditions</li> </ul>
<ul style="list-style-type: none"> <li>Comprehensive color portfolio</li> </ul>	<ul style="list-style-type: none"> <li>Higher throughput</li> <li>Customer satisfaction</li> </ul>




Fast

Slow



100:50:10-50  
2K Acrylic Topcoat  
2K Hardener  
Acrylic Thinner




1-2-3




1.3 – 1.4 mm



2 – 3 coats



5 – 10 mins.



5-6 hours @ 20°C  
20-25 mins. @60°C

# AKRİPOL

# AkzoNobel