

AKRIPOL Ultraguard

Akripol Ultraguard 2-pack epoxy primer has excellent adhesion to steel, galvanized steel and aluminum vehicle parts.

It is designed to be used in vehicle refinishes with outstanding corrosion resistance and physical durability properties.

Ultraguard epoxy primer can be used as both sanding version or non – sanding version.

It has better film build when used as sanding version epoxy primer.



Features

Benefits

- Excellent adhesion to steel, galvanized steel and aluminum vehicle parts

- One product for multi type of repairs
- Less material stock
- Material saving

- High corrosion resistance and durability


- User friendly
- Warranty repair

- Sanding and non-sanding version

- Less material stock
- Reduced cycle times
- One product for multi type of repairs



Sanding version




4:1:5-25
Epoxy Primer
Epoxy Hardener
Epoxy Thinner



1.6 - 1.8 mm



2 - 3 coats



24 h @ 20°C
45 mins. @ 60°C




P 400
P 500




P 800
P 1000

Non – sanding version




4:1:1
Epoxy Primer
Epoxy Hardener
Epoxy Thinner




1.6 - 1.8 mm



1 - 2 coats



5 – 10 mins.



Minimum 45 mins @ 20°C
Maximum 24 h @ 20°C

AKRIPOL

AkzoNobel